

2006 BMW R 1200 GS

MSRP: \$14,700.00*



Copyright 2005 BMW of North America, LLC., Woodcliff Lake, New Jersey all rights reserved.

*Actual price determined by dealer. MSRP includes equalized freight charges and PDI. Price excludes taxes, license, options and handling charge. Prices and specifications subject to change without notice.

Engine		Wheels and Tires	
Type	Air-cooled/oil-cooled Boxer twin-cylinder	Front Wheel	2.50 x 19 cast alloy, five double-spoke
Bore x Stroke	101.0 mm x 73.0 mm	Rear Wheel	4.00 x 17 cast alloy, five double-spoke
Displacement	1170 cc	Front Tire	110/80 x 19 tubeless
Horsepower	100 bhp @ 7250 rpm	Rear Tire	150/70 x 17 tubeless
Torque	85 lb/ft @ 5500 rpm	Dimensions	
Compression Ratio	11.0 :1	Overall Length	87.0 inches
Valve Gear	Chain-driven, high cam, OHV, w/adj. rocker arms	Overall Width	36.0 inches
Valves	2 x 36 mm intake / 2 x 31 mm exhaust	Wheelbase	59.8 inches
Valves / Cylinder	Four	Ground Clearance	7.3 inches
Engine Oil Capacity	4.2 quarts	Seat Height	33.1 inches
Engine Management	BMW Engine Controller - BMS K	Steering Angle	62.9 degrees
Fuel Requirement	Premium Unleaded	Front Wheel Trail	4.3 inches
Fuel Tank	HDPE, internal pump and internal filter	Weight - Dry	439 lbs. excluding options & accessories
Fuel Capacity	5.2 U.S. gallons including 1 gallon reserve	Weight - Wet	496 lbs. excluding options & accessories
Charging System	600 Watts @ 14 Volts	Maximum Load	936 lbs. GVWR
Battery	12 Volts 14 Amps/hour low maintenance	Standard Colors	
Cooling System	Air and thermostatically controlled oil cooling	Code Price	Description
Drivetrain		933 N / C	Granit Gray Metallic
Primary Drive	1:1.823	947 N / C	Ocean Blue Metallic
Clutch	180 mm dry, single plate with hydraulic actuation	950 N / C	Rock Red Metallic
1st Gear Ratio	2.28:1	952 N / C	Desert Yellow Metallic
2nd Gear Ratio	1.58:1	Standard Equipment	
3rd Gear Ratio	1.26:1	773 N / C	Seat - Black
4th Gear Ratio	1.03:1	Available Equipment	
5th Gear Ratio	0.90:1	164 N / C	Seat - Gray
6th Gear Ratio	0.81:1	340 \$125	Chrome Exhaust Pipe
Final Drive System	Enclosed driveshaft with two universal joints	419 N / C	Side Cover - Gray
Final Drive Ratio	2.82:1	420 N / C	Side Cover - Black
Frame and Suspension		519 \$200.00	Heated Hand Grips
Frame	Three-part, engine/cast aluminum/tubular steel	588 \$50.00	Clear Turn Signal Lenses
Front Suspension	BMW Telelever	589 \$70.00	Hand Protection
Front Travel	7.5 inches	603 \$225.00	Anti Theft Alarm
Rear Suspension	BMW EVO Paralever	645 \$995.00	ABS - Partial Integral
Rear Travel	7.9 inches	681 \$155.00	Saddle Bag Mounts
Brakes		771 \$495.00	Cross-Spoke Wheels
Brake System	BMW EVO with partial integral ABS	776 \$N / C	Seat - Low (31.9 inches)
Front Brakes	Two, four-piston fixed calipers		
Front Rotor	12.0 inch dual floating rotors		
Rear Brake	Single, two-piston floating caliper		
Rear Rotor	10.4 inch single, fixed rotor		
Actuation Method	Hydraulic, DOT 4 fluid type		